

Errors

The following errors are returned by C1 Core's REST API:

Error message	c1-core	c1-auth	Description
<code>request_error</code>	X	X	Generic error processing the request. See log or error description for more information.
<code>account_locked</code>		X	The user's account is locked. Only returned by <code>POST /auth</code> .
<code>client_unknown</code>		X	The client ID is unknown.
<code>data_error</code>	X	X	Error in request data.
<code>element_unknown</code>	X	X	The element is unknown.
<code>entry_exists</code>	X	X	An entry with this ID already exists.
<code>invalid_path</code>	X	X	The path of the URI is invalid.
<code>invalid_http_method</code>	X	X	The path exists but the HTTP method is invalid.
<code>missing_data_field</code>	X	X	Missing field in request data.
<code>missing_header_field</code>	X	X	A required header was not found in the request.
<code>module_request_error</code>	X	X	Error executing RPC command on module. See log or error description for more information.
<code>password_change_required</code>		X	The user's password must be changed. Only returned by <code>POST /auth</code> .
<code>password_hacked</code>	X	X	The user's password is on a list of hacked passwords.

Error message	c1- core	c1- auth	Description
token_expired	X	X	The provided token has expired.
user_unknown	X	X	The user is unknown.

This list is complete. No other errors are returned, so this list can be used to create localized error messages.